# DEDICATED TO MARINE HIGH-RESOLUTION SEISMIC PROCESSING







# GET MORE OUT OF YOUR HIGH-RESOLUTION MARINE SEISMIC DATA!

processing power than any typical piece of the quality of high-resolution marine seismic data software provided by equipment vendors. While significantly. their main expertise is in electronics and hardware, we are a dedicated geophysical Single or multi-channel, boomer, sparker or software company. Our team of geophysicists and airgun, 2D or 3D -- high-resolution marine data can software engineers have got an extensive benefit from in-depth processing in RadExPro, experience both in processing of hi-res marine revealing more details and extracting more seismic data, and in programing of algorithms to geological information. advance and facilitate it.

We bring together our own processing expertise and state-of-the-art processing techniques borrowed from oil-and-gas seismic industry. For only a fraction of the cost of any big seismic processing system available on the market, we


RadExPro gives you much more seismic offer a software solution capable of improving



### **DEMULTIPLE**

Remove disturbing multiples from your boomer and channel data acquired at relatively short offsets. For The algorithm was specially designed for single- standard SRME technique is available.


sparker records with Zero-Offset Demultiple routine. bigger systems with more channels, the industry-



# SharpSeis DEGHOSTING / BROADBAND PROCESSING


our SharpSeis deghosting solution. Suitable for both making the record true broad-band. conventional and deep-tow HR/UHR seismic data, the

Make your seismics look really sharp and crispy using technique dramatically improves data resolution




#### **DEBUBBLING**

Remove bubble noise efficiently from your data easy to use and is based on Kholmogoroff spectral without affecting the wavelet. The algorithm is fairy factorization.



### **HIGH-RESOLUTION MARINE STATICS**

HR/UHR marine seismic data, especially the higher corrections calculated and smoothed in different frequencies, can be significantly affected by sea domains (common shot gather, common receiver swelling as well as any instabilities in towing gather), with subtraction of seafloor trend. Below is an conditions, which can compromise the resolution of example of CMP stack before and after static the record and ruin continuity of reflections. These corrections: 48 channels @ 1 m interval, sparker destructive effects can be eliminated by marine static source.



## MINIMUM RECOMMENDED SYSTEM REQUIREMENTS

Intel Core i5 CPU 16 GB RAM Windows 7/8/10/11 64-bit OS



RadExPro seismic software LLC Tbilisi, GEORGIA



RadExPro Europe OÜ Tallinn, ESTONIA



sales@radexpro.com support@radexpro.com www.radexpro.com +995 557 659289